

GOLD STAR UNDERCOAT

(Alkyd Based Primer)

PAINTCAM

Technical Data Sheet

09.12.2020

DESCRIPTION	: A general purpose Alkyd and solvent based undercoat, with matt finish and good filling property.
COLOUR	: White, special color if requested.
FINISH	: Flat (Mate) finish.
USES	: Excellent general purpose undercoat for both interior and exterior applications especially on wood and Gypsum boards. Also suitable for benches, bathrooms, laundries. Avoid direct application on concrete for chemical reasons.

APPLICATION DATA

METHOD	: Rolle, brush or spray gun.
THEORETICAL COVERAGE	: 10-13 m ² / liter at 75-100 micron wet thickness.
DILUTION	: 15 – 20 % with white spirit.
SURFACE PREPARATION	: Ensure surface is clean, dry and stable using the following suggested surface treatments: <ul style="list-style-type: none">• Moisture : There must not be any water residue on the surface of the substrate. Moisture must be <4% before application.• Unstable matter : Remove loose bonding film, dirt, peeling paint, etc by a mechanical means such as power brush or scraper, whichever is suitable.• Contaminants : Remove dust and foreign matter by cleaning with damp cloth. Remove oil or grease using solvent or mild detergent. Allow surface to dry.• Hairline cracks : Fill cracks with suitable putty or filler.
DRYING TIME	: 4 hours to touch .
OVERCOATING TIME	: 16 hours based at normal condition
CLEANING	: All equipment should be cleaned with White Spirit immediately after use .

GENERAL INFORMATION

SOLID CONTENT	: 75 ± 2%
SPECIFIC GRAVITY	: 1.5 ± 0.02 gr/liter
PACKING	: 3.7 Liters , 18 Litres.

GOLD STAR UNDERCOAT

(Alkyd Based Primer)

PAINTCAM

Technical Data Sheet

09.12.2020

- STORAGE** : Store in a tightly sealed container in a cool, dry place
- SHELF LIFE** : Up to 24 months in a tightly sealed container
- PRECAUTION** : Ensure good ventilation during application and drying of paint. Avoid direct contact with skin. Use appropriate personal protective equipment .

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

Enquiries / Contact Details :

Customer Service +237 6 91 08 08 08 (Main Line)

Green Line 8050

www.paintcam.com